

LAMORA HLP 32, 46, 68

Hydraulic oils acc. to DIN 51524 part 2



Benefits for your application

- HLP hydraulic oils acc. to DIN 51524, part 2
- Good wear protection
- Service temperature range from –12°C to 120°C

Description

LAMORA HLP are hydraulic oils based on mineral oils. They comply with the HLP requirements of DIN 51 524, part 2 and reduce friction and wear.

previous oil fill might reduce their performance. We therefore recommend cleaning the oil circuit thoroughly before applying LAMORA HLP oils for the first time.

Application

LAMORA HLP have been designed for use as hydraulic oils.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.

Application notes

LAMORA HLP oils are miscible with mineral oil-based hydraulic fluids. However, it should be taken into consideration that mixing LAMORA HLP oils with residual quantities of the


Pack sizes	LAMORA HLP 32	LAMORA HLP 46	LAMORA HLP 68
Canister 20 l	+	+	+
Drum 200 l	+	+	+

Product data	LAMORA HLP 32	LAMORA HLP 46	LAMORA HLP 68
Article number	031007	031008	031009
Chemical composition, type of oil	mineral oil	mineral oil	mineral oil
Lower service temperature	-15 °C / 5 °F	-12 °C / 10.4 °F	-12 °C / 10.4 °F
Upper service temperature	120 °C / 248 °F	120 °C / 248 °F	120 °C / 248 °F
Appearance	clear	clear	clear
Colour space	yellow	yellow	yellow
Density, DIN 51757, 20 °C	approx. 0.88 g/cm³	approx. 0.87 g/cm³	approx. 0.88 g/cm³
Kinematic viscosity, DIN 51562 pt. 01/ASTM D-445/ASTM D 7042, 40 °C	approx. 32 mm²/s	approx. 46 mm²/s	approx. 68 mm²/s
Pour point, DIN ISO 3016	<= -18 °C	<= -15 °C	<= -12 °C
Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx.	36 months	36 months	36 months



LAMORA HLP 32, 46, 68

Hydraulic oils acc. to DIN 51524 part 2



Klüber Lubrication – your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

**Klüber Lubrication München SE & Co. KG /
Geisenhausenerstraße 7 / 81379 München / Germany /
phone +49 89 7876-0 / fax +49 89 7876-333.**

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.