

Castrol Longtime PD

High performance bearing grease

Description

Castrol Longtime™ PD range are lithium based greases containing highly refined mineral oils and fortified with the Microflux Trans (MFT) additive system. The MFT additive technology provides optimum wear protection and an extremely low coefficient of friction even under extremes of pressure, vibration, shock loads, at high or low speeds or varying micro-smoothing of the friction surfaces.

Under severe load, components of the MFT additive combination are activated and diffuse into the surfaces initiating an improvement of their friction characteristics through plastic deformation. The organic reaction products become a component of the tribopolymer system. Unlike the case with conventional lubricants, the tribopolymers formed by MFT are long-chained compounds with excellent lubricity and adhesion. The load carrying area is improved, a hydrodynamic lubrication film is easier to maintain. This unique physio-chemical reaction achieves a non-sacrificial micro-smoothing of the friction surfaces.

Application

Longtime PD can be used for long term or lifetime lubrication even under the most difficult operating conditions such as extreme pressure, vibrations, shock loads and a wide temperature range in highly loaded rolling and sliding bearings. They can also be used in bearings of spinning and grinding spindles, for gear motors exposed to shock loads, in screening/wood shaping machines and for bearing surfaces of printing plates.

These greases are also suitable for bearings with a rotating outer ring and undergoing high stresses due to centrifugal load, e.g. in spreader rolls, roll neck bearings in steel mills, and for bearings with changing rotational directions or slewing movements. They are also used in curved teeth couplings and centralised lubricating systems.

Longtime PD 0 and PD 00 can be used as a semi-fluid grease lubricant in gears such as flange, drum-type and worm gears. It is also suitable for use in gears without oil-tight enclosures, gear wheels and rolling bearings with a grease reservoir.

Advantages

- High load bearing capacity – extends the operating period under high loads leading to optimum wear protection
- Superior lubrication and surface smoothing effects due to MFT reduced failures leading to less downtime and repair work. MFT can result in prolonging the life of damaged components/bearings
- Establishment of a protective layer of MFT – this additive system can effectively increase the load bearing area, thus reducing unit pressures, operating temperatures and wear, increasing service life of both parts and lubricant
- Improved bearing surfaces for longer service life result from the 'running in' effect of MFT
- Extremely low coefficients of friction – generating energy savings and reduced noise levels
- Multi-functional – Longtime PD 0 and PD 00 are highly recommended for anti-friction bearings with grease reservoir and for leaky gearboxes
- Easily pumpable in central lubrication systems – does not channel on gears running at high speeds when using PD 0 and PD 00
- Exceptional water resistance – coating film stays on the surface even in presence of water; even when exposed to the action of hot and chemically active process water

Typical Characteristics

Test	Method	Units	PD 00	PD 0	PD 1	PD 2
Appearance, Visual	-	-	Brown	Brown	Brown	Brown
Thickener Type	-	-	Lithium	Lithium	Lithium	Lithium
Base Oil Type	-	-	Mineral oil	Mineral oil	Mineral oil	Mineral oil
NLGI Grade	-	-	0	0	1	2
Density @ 20°C/68°F	ASTM D1475	g/ml	0.91	0.89	0.89	0.89
Worked Penetration, 60 Strokes @ 25°C/77°F	ISO 2137 ASTM D217	0.1mm	400-430	355-385	310-340	265-295
Worked Penetration, 100,000 Strokes @ 25°C/77°F, Change From 60 Strokes	ISO 2137 ASTM D217	0.1mm	NA	NA	<20	<20
Dropping Point	ISO 2176 ASTM D2265	°C/°F	NA	NA	190/374	200/392
Base Oil Viscosity @ 40°C/104°F	ISO 3104 ASTM D 445	mm²/s	130	130	95	95
Copper Corrosion, 24 hrs, 100°C/212°F	ISO 2160 ASTM D4048	Rating	1b	1b	1b	1b
SRV [®] Test Run: 400N, 50°C/122°F/ball/disc/2hr Coefficient of friction Ball/Scar Diameter	ASTM D 5707 DIN 51834	- mm	0.08 0.65	0.07 0.65	0.07 0.65	0.07 0.65
Flow Pressure at -35°C/-31°F	DIN 51805	hPa	500	1000	1100	1200
Water Resistance, 90°C/194°F, 3h	DIN 51807-1	Rating	NA	NA	1	1
DIN Classification	DIN 51502	-	KP 00 N-40	KP 0 N-40	KP 1 N-30	KP 2 N-30
ISO Classification	ISO 6743/9	-	L-XDDBH-00	L-XDDBH-0	L-XCDHB-1	L-XCDHB-2

Subject to usual manufacturing tolerances.

Additional Information

In order to minimise potential incompatibilities when converting to a new grease, all previous lubricant should be removed as much as possible prior to operation. During initial operation, re-lubrication intervals should be monitored closely to ensure all previous lubricant is purged.

Castrol, Longtime, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial
www.castrol.com/industrial