

SYNTHESO W Spray

Rust preventive, separating and lubricating wax



Benefits for your application

- Versatile product for maintenance, lubrication and preservation
- Time-saving and clean application by means of spray can including spare spray nozzle and extension tube

Description

SYNTHESO W Spray is a versatile separating, lubricating and sliding agent based on paraffin waxes of high molecular weight dissolved/dispersed in volatile hydrocarbons. SYNTHESO Spray forms a protective film resistant to salt water when dry.

Application

SYNTHESO W Spray can be used for the maintenance, lubrication and preservation of tools, bearings, guides and chains in paper, textile or office machines, as well as in automotive engineering for joints, guides and seat rails, and many other applications. SYNTHESO W Spray is also suitable for use as a separating and lubricating wax on cutting knives in film stretchers, paper-making machinery and corrugators.

Application notes

In order to attain a thin and uniform film, activate spray can only briefly. Keep can vertical and apply a thin film from approx. 20 cm. For higher spraying accuracy, use the spray nozzle complete with extension tube. Shake can well before spraying to prevent separation of component parts. Provide for adequate ventilation while spraying in order to prevent the propellant from forming explosive mixtures. Do not spray towards naked flames, incandescent or hot objects. Please observe additional application notes outlined in the material safety data sheet or on the product container.

Material safety data sheets

Material safety data sheets can be requested via our website www.klueber.com. You may also obtain them through your contact person at Klüber Lubrication.


| Pack sizes | SYNTHESO W Spray |
|--------------------|------------------|
| Aerosol can 250 ml | + |

| Product data | SYNTHESO W Spray |
|--|------------------|
| Article number | 081034 |
| Chemical composition, solid lubricant | wax |
| Chemical composition, solvent | hydrocarbon |
| Chemical composition, propellant | propane-butane |
| Melting point, DIN ISO 3841 | approx. 40 °C |
| Colour space | white |
| Minimum shelf life from the date of manufacture - in a dry, frost-free place and in the unopened original container, approx. | 24 months |



SYNTHESO W Spray

Rust preventive, separating and lubricating wax



Klüber Lubrication - your global specialist

Innovative tribological solutions are our passion. Through personal contact and consultation, we help our customers to be successful worldwide, in all industries and markets. With our ambitious technical concepts and experienced, competent staff we have been fulfilling increasingly demanding requirements by manufacturing efficient high-performance lubricants for more than 80 years.

Klüber Lubrication München SE & Co. KG / Geisenhausenerstraße 7 / 81379 München / Germany / phone +49 89 7876-0 / fax +49 89 7876-333.

The data in this document is based on our general experience and knowledge at the time of publication and is intended to give information of possible applications to a reader with technical experience. It constitutes neither an assurance of product properties nor does it release the user from the obligation of performing preliminary field tests with the product selected for a specific application. All data are guide values which depend on the lubricant's composition, the intended use and the application method. The technical values of lubricants change depending on the mechanical, dynamical, chemical and thermal loads, time and pressure. These changes may affect the function of a component. We recommend contacting us to discuss your specific application. If possible we will be pleased to provide a sample for testing on request. Klüber products are continually improved. Therefore, Klüber Lubrication reserves the right to change all the technical data in this document at any time without notice.

Publisher and Copyright: Klüber Lubrication München SE & Co. KG. Reprints, total or in part, are permitted only prior consultation with Klüber Lubrication München SE & Co. KG and if source is indicated and voucher copy is forwarded.

