Product Data

Castrol Hysol RD

High performance semi-synthetic metalworking fluid

Description

Castrol Hysol™ RD is a high performance chlorine free semi-synthetic metalworking fluid. It contains a unique additive package that works in synergy to enhance machining performance and surface finish, provide excellent product stability, improve bio-resistance properties and lower the overall operations costs.

Hysol RD is suitable for large central systems and single sump machines.

Application

Castrol Hysol RD is especially designed for machining of cast iron and low-medium alloyed steel.

	Cast Iron	Low-medium alloyed steel	High alloyed - stainless steel	Aluminium alloys	Magnesium alloys	Yellow metals
Grinding	111	44	11			
Milling, Turning (general machining)	111	11				
Drilling	111	4				
Reaming, Tapping	111	\				
Broaching	111	√				

Advantages

- Chlorine and nitrite free to fulfill your local legislation, waste treatment and environmental requirements
- Resists fungal and bacterial attack to extend fluid life and reduce maintenance and machine downtime
- Low foam in recommended water conditions
- Excellent anti-corrosion properties to protect machine tools and parts
- Advanced lubricity compounds ensure improved tool life and part quality
- Excellent wetting properties reduce coolant drag out and deliver clean machine tools and components

Page 1 / 2 20 July 2010, Version 1

Typical Characteristics

	Test Method	Unit	Value
Concentrate			
Appearance	Visual		Amber
Mineral oil content	Calculated	Wt%	35
Emulsion			
Appearance	Visual		Transparent
pH (5%)	DIN 51369		9,0
Refractometer Factor			1,1

	Boron	Formaldehyde releasing agent	EP-Ester	Amines	Chlorine
Additives	*	*	-	٨	-

Recommended Concentrations

Grinding 4-6% 5-7% General Machining 6-8% Drilling Reaming and tapping 6-8% Broaching 6-8%

5-20 °dH Water range

Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress.

Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always. For more details, please refer the product safety data sheet.

Castrol, Hysol, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material.

All products, services and information supplied are provided under our standard conditions of sale.

You should consult our local representative if you require any further information.

BP Europa SE – Industrial Lubricants & Services, Erkelenzer Str. 20, 41179 Mönchengladbach Tel: +49 (0)2161 909-30 Fax: +49 (0)2161 909-481

www.castrol.com