

Castrol Iloform FST 16

Chlorine free neat forming oil

Description

Castrol Iloform™ FST 16 is a medium viscosity, neat forming oil containing high levels of advanced lubricity and extreme pressure additives. It is free of chlorine and heavy metals, such as Barium.

Application

Iloform FST 16 has been specifically developed for medium duty deep drawing operations on carbon steel and stainless steel parts. The product shows reliable performance at medium steel sheet metal thickness.

The enhanced lubrication package also allows use in medium duty fineblanking applications.

Iloform FST 16 is designed to be used as received.

Advantages

- Superior adhesion and wetting performance provide homogenous lubricating film which delivers best machining results, even on difficult geometries.
- High resistance to pressure and high protection against wear enables long tool and die life and thus cuts downtime and tooling costs.
- Good cleanability and demulsifying properties enable long bath-life of subsequent cleaning processes
- Reliable corrosion protection reduces scrap rate.
- Chlorine- and heavy metal-free technology improves the environmental profile and minimises waste disposal costs.

Typical Characteristics

	Test Method	Unit	Value
Appearance	Visual	–	Dark brown liquid
Density @ 15°C	DIN 51 757	kg/m ³	945
Viscosity @ 40°C)	DIN 51 562	mm ² /s	93
Flash Point	ISO 2592	°C	> 170

Ester	Sulphur	Phosphorous	Chlorine	Other
✓✓	✓✓✓	✓✓		

User Advice

Iloform FST 16 is not suitable for use on yellow metals

Iloform FST 16 can be removed by using a petroleum solvent or alkaline process cleaner, all available from Castrol.

Storage

To avoid product deterioration, keep the container/drum tightly sealed always. Prevent any frost and water ingress.

Store it in a cool and dry place away from direct sunlight. It is preferable to store the product indoors always.

For more details, please refer the product safety data sheet.

Castrol, Iloform FST, and the Castrol logo are trademarks of Castrol Limited, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material.

All products, services and information supplied are provided under our standard conditions of sale.

You should consult our local representative if you require any further information.

Deutsche BP AG – Industrial Lubricants & Services, Erkelenzer Str. 20, 41179 Mönchengladbach

Tel: +49 (0)2161 909-30 Fax: +49 (0)2161 909-481

www.castrol.com