

# RUST VETO 28/FC

## Data Sheet

### PROTECTIVE FLUID WITH WAXY FILM

RUST VETO 28/FC is a specifically designed product to be applied on the pieces coming from mechanical working operations, surface treatments, heat treatments, to provide good rust prevention characteristics.

#### CHEMICAL -PHYSICAL CHARACTERISTICS

Appearance	Clear liquid
Colour	Amber
Flammability COC	100°C
Covering power per kg.	m <sup>2</sup> 100 approx
Protection Time	Indoor : 10 months Outdoor: not suggested
Type of film	Colourless oily film
Film thickness	4 μ
Removal of film	Cold solvents or alkaline solutions

#### HOW TO USE

RUST VETO 28/FC can be applied through specific drips connected on coilers and cutting lines, by immersion, by brush, through electrostatic device or sprayed. (On rolling machines the product is directly sprayed on working rolls).

#### PACKAGING

RUST VETO 28/FC is supplied in 180 kilo drums and in bulk.

## STORAGE

RUST VETO 28/FC maintains its chemical-physical and technical characteristics if stored in a sheltered place at a temperature of  $-5^{\circ}\text{C}+40^{\circ}\text{C}$  for a maximum period of twelve months.

## HEALTH & SAFETY

No toxic or carcinogenic, teratogenic or mutagenic known materials are contained in RUST VETO 28/FC such as nitrosamines, phenols, polychlorinated diphenyl, heavy metals, poly nuclear hydrocarbons.

For the handling of RUST VETO 28/FC pay normal care usually given to industrial products.

## WASTE TREATMENT

RUST VETO 28/FC cannot be directly discharged. Follow national or local instructions.

G/02: Approval: Dr. G.Petta
-----------------------------