

RUST VETO 4214 - RUST VETO 4214 HF RUST VETO 4225

Data Sheet

RUST PREVENTIVES

MAIN FEATURES

1. Exceptionally stable in wet conditions, particularly in case of alkalyne and/or acid emulsion or solutions left on parts
2. Prolonged effectiveness where rinsing is not always thorough. It releases displaced water within minutes and, on evaporation, leaves a very thin, transparent protective film
3. Provides indoor protection for as long as twelve months, particularly if parts are packaged
4. Particularly suitable for application following electroplating, surface conversion processes, wet tumbling
5. Can be applied by spray, dip or brush at temperatures ranging 4–35°C
6. Provides excellent long-term protection, though it is not intended for long-term outdoor protection

	RUST VETO 4214	RUST VETO 4214 HF	RUST VETO 4225
Type of film	Oily transparent		
Flammability [TOC]	40°C	70°C	130°C
Film thickness [approx.]	0.0025 mm	0.0030 mm	0.0040 mm
Drying time	1-2 hours	2-5 hours	3-6- hours
Covering power	100 m ² /litre	90 m ² /litre	90m ² /litre
Application	Immersion, spray, brush		
Protection time	12 month in a sheltered place - Not recommended in open space		

RUST VETO 4214, RUST VETO 4214 HF, RUST VETO 4225 are different mainly for the quantity of solvent contained and consequently their flash point vary; they can be used in change.

Note: It is recommended the use of closed tanks when RUST VETO 4214 and RUST VETO 4214 HF are applied by dipping, to avoid the evaporation of the solvent while not used. For the same reason drums containing the product should be kept closed.

REMOVAL

RUST VETO 4214, RUST VETO 4214 HF, RUST VETO 4225 can be removed by washing with cold solvent or hot alkaline solutions.

SAFETY PRECAUTIONS

RUST VETO 4214, RUST VETO 4214 HF, RUST VETO 4225 contain petroleum hydrocarbon. Avoid prolonged breathing and/or skin contact. Take ordinary protective measures against fire danger and keep working areas well ventilated.

RUST VETO 4214 IS A FLAMMABLE PRODUCT : STORE IN SUITABLE ROOMS.

STORAGE

RUST VETO 4214, RUST VETO 4214 HF, RUST VETO 4225 maintain their chemical-physical and technical characteristics if stored in a sheltered place for a maximum period of twelve months.

If stored below 4°C bring back to use temperature before applying.

WASTE TREATMENT

RUST VETO 4214, RUST VETO 4214 HF, RUST VETO 4225 cannot be directly discharged. Follow national or local instructions.

G/03 DR. D. PETTA