* PRODUCT INFORMATION

HUSKEY™ 341

COPPER ANTI-SEIZE COMPOUND

DESCRIPTION

HUSKEY 341 Anti-Seize is a general purpose, economical, industrial anti-seize and lubricating paste containing micro-sized copper particles and graphite in a special no-melt petroleum base grease. HUSKEY 341 Anti-Seize adheres well to metal surfaces and offers exceptional wear resistance. Therefore it can provide outstanding protection against galling, seizing and corrosion on metal surfaces even under the most extreme of heat, pressure, steam and water exposure.

USAGE

HUSKEY 341 was designed as a preventative maintenance tool providing complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures up to +1800°F. **HUSKEY 341** was formulated to fit a wide variety of metal working, automotive, oilfield, construction and farm equipment applications. A few such examples include:

- NUTS. BOLTS & SCREWS
- SENSORS
- SPROCKETS & CHAINS
- FORGING DIES
- SPLINES & GEARS
- BATTERY POSTS

- GASKETS
- KEYWAYS & SHAFTS
- BRAKE CAMS & PINS
- CONVEYORS
- VALVE ASSEMBLIES
- SPARK PLUGS

CAUTION: Do Not Use On Oxygen Systems

ADVANTAGES

HUSKEY 341 is unlike conventional products on the market because the maximum blend of metallic solids, proprietary dry-film lubricants and anti-galling agents have been homogenized into a specially designed petroleum base grease which does not contain clay or soap base thickeners. This helps to provide a superior product that will not melt and run out after application. In addition, this stable blend is unaffected by severe temperatures, vibration, expansion and contraction. Other advantages include:

- PROTECTS UP TO +1800 °F.
- REDUCES TORQUE
- PREVENTS CARBON FUSION
- PREVENTS RUST & CORROSION
- **EXCELLENT LUBRICITY**
- PREVENTS GALLING & SEIZING
- STEAM & WATER RESISTANT
- CHEMICAL RESISTANT
- EXTREME PRESSURE LUBRICANT
- NON-MELTING



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860 (951) 340-4000 · Fax: (951) 340-4011

(888) 4-HUSKEY · www.huskey.com

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056 (330) 425-2567 · Fax: (330) 425-9637

(800) 238-LUBE

* PRODUCT INFORMATION

TYPICAL PROPERTIES

DESCRIPTION

HUSKEY Product:341 Anti-seizeColor:Dark CopperBase OilPetroleumThickenerSyntheticTextureButtery

<u>TESTS</u>	ASTM TEST	RESULTS
	<u>METHOD</u>	
N.L.G.I. Grade		1
Penetration		
Unworked	D-217	325
Worked, 60 Strokes		335
Base Oils Viscosity,		
cSt @ 40°C	D-445	215
cSt @ 100°C	D-445	13
Pour Point, °F	D-97	0
Flash Point °F	D-92	420
Dropping Point °F	D-566	None

PACKAGE AVAILABILITY

1 gal. Pails, 5 gal. Pails, 15 gal. Keg and 55 gal. Drum (Custom Packaging Available on Request)

The name of this product or group of products is for product identification only. HUSK-ITT Corp. makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT Corp. sales personnel are not authorized to amend this warranty limitation 07/16



HUSKEY Specialty Lubricants

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

Western Region Office:

1580 Industrial Avenue, Norco, California 92860 (951) 340-4000 · Fax: (951) 340-4011 (888) 4-HUSKEY · www.huskey.com Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056 (330) 425-2567 · Fax: (330) 425-9637 (800) 238-LUBE