



Search...

Can't find what you're looking for?  
Search for it here.

- [HOME](#)  
 [PRODUCTS ▼](#)  
 [INDUSTRIES ▼](#)  
 [BROCHURES ▼](#)  
 [OUR COMPANIES](#)  
[CONTACT](#)

## HUSKEY™ 341 COPPER ANTI-SEIZE COMPOUND

### Description

**HUSKEY 341 COPPER ANTI-SEIZE** is a heavy-duty, economical industrial anti-seize and lubricating paste containing a balanced blend of copper and graphite powder in a no-melt petroleum base grease. **HUSKEY 341** leaves a protective film that protects metal parts and fasteners against extreme conditions of steam, chemicals, water and high temperatures to 2000°F.

### Advantages

**HUSKEY 341** is unlike conventional products on the market because the maximum blend of metallic solids, proprietary dry-film lubricants and anti-galling agents have been homogenized into a specially designed petroleum base grease which does not contain clay or soap base thickeners. This helps to provide a superior product that will not melt and run out after application. In addition, this stable blend is unaffected by severe temperatures, vibration, expansion and contraction. Other advantages include:

- PROTECTS UP TO +1800 °F.
- REDUCES TORQUE
- PREVENTS CARBON FUSION
- PREVENTS RUST & CORROSION
- EXCELLENT LUBRICITY
- PREVENTS GALLING & SEIZING
- STEAM & WATER RESISTANT
- CHEMICAL RESISTANT
- EXTREME PRESSURE LUBRICANT
- NON-MELTING

### Usage

**HUSKEY 341** was designed as a preventative maintenance tool providing complete parts protection on threaded fittings and all metal surfaces subjected to harsh environments or high temperatures up to +1800°F. **HUSKEY 341** was formulated to fit a wide variety of metal working, automotive, oilfield, construction and farm equipment applications. A few such examples include.

- NUTS, BOLTS & SCREWS
- SENSORS
- SPROCKETS & CHAINS
- FORGING DIES
- SPLINES & GEARS
- BATTERY POSTS
- GASKETS
- KEYWAYS & SHAFTS
- BRAKE CAMS & PINS
- CONVEYORS
- VALVE ASSEMBLIES
- SPARK PLUGS

**CAUTION:** Do Not Use On Oxygen Systems

## Package Availability

- 1 gal. Pail
- 2 gal. Pail
- 3.5 gal. Pail
- 5 gal. Pail
- 15 gal. Keg
- 55 gal. Drum
- Custom Packaging Available Upon Request

## Typical Specifications

**Product:** 341 Anti-seize

**Base Oil:** Petroleum

**Thickener:** Synthetic

**Color:** Dark Copper

**Texture:** Buttery

Test	ASTM Test Method	Results
N.L.G.L. Grade		1
Penetration		
<i>Unworked</i>	D-217	325
<i>Worked 60 strokes</i>		335
Base Oils Viscosity,		
<i>SUS @ 100 °F</i>	D-445	990
<i>SUS @ 210 °F</i>	D-445	66
Pour Point °F	D-96	0
Flash Point	D-92	420
Dropping Point °F	D-566	None

[SAFETY DATA SHEET](#)

[Call for a Quote](#)

The name of this product or group of products is for product identification only. HUSK-ITT Corporation. makes no warranties, representations or conditions of any kind expressed or implied, whether for merchant ability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT Corporation sales personnel are not authorized to amend this warranty limitation.

[Return](#)

Copyright 2018 by HUSK-ITT Corporation. Login