

# \* PRODUCT INFORMATION \*

## **HUSKEY™ COOLPLEX GREASE**

### **DESCRIPTION**

**HUSKEY COOLPLEX GREASE** is a premium quality, all-purpose, non-melting grease. It is a blend of the highest quality base oils and thickeners available. Treated with state of the art additives, they provide lasting protection against rust, corrosion and oxidation. The most important built-in feature in **HUSKEY COOLPLEX** is the tenacious quality of its polymer additives. Such a feature helps produce more uniform friction drag, cushions shock loading and minimizes wear. **HUSKEY COOLPLEX** with its “cling to” ability will stay on the metal surface much longer than most conventional greases on the market today, resulting in longer-lasting lubricity, with fewer lubrication intervals.

### **USAGE**

**HUSKEY COOLPLEX GREASE** may be utilized for applications where a multi-purpose No. 2 grade grease is employed. It was designed to fit a wide variety of automotive, industrial, agricultural and household applications such as:

- Wheel bearings
- Ball joints
- Universal joints
- Electric motors
- Fans & blowers
- Heavy-duty trucks
- Guide rail and sliding surfaces
- Garden tractors
- Fifth wheels
- Conveyors

### **ADVANTAGES**

- Non-melting
- Low coefficient of friction
- Wider temperature range
- Labor saving
- Reduced wear
- Extremely water resistant

### **PACKAGE AVAILABILITY**

Convenient disposable gun-loaded 14 oz. Cartridges  
5 gal. Pail, 15 gal. Keg, and 55 gal. Drum



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE

# \* PRODUCT INFORMATION \*

## TYPICAL PROPERTIES

<b>DESCRIPTION</b>	<b>HUSKEY</b> Product:	Coolplex
	Color:	Amber
	Base Oil:	Petroleum
	Thickener:	Synthetic
	Texture:	Smooth & Tenacious

<u>TEST</u>	<u>ASTM METHOD</u>	<u>TYPICAL RESULTS</u>
N.L.G.I GRADE	----	2
Worked Penetration, 60 strokes	D-217	265-295
Base Oil Viscosity, SUS @ 100°F SUS @ 210°F cSt @ 40°C. cSt @ 100°C.	D-445	755 78 144 14.6
Pour Point, °F	D-97	7
Flash Point, °F	D-92	545
Dropping Point, °F	D-566	NONE
Corrosion Preventative Test	D-1743	PASS
Timken OK Load, lbs.	D-2509	40

The name of this product or group of products is for product identification only. HUSK-ITT CORPORATION makes no warranties, representations or conditions of any kind expressed or implied whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT CORPORATION sales personnel are not authorized to amend this warranty limitation.

5/11



## **HUSKEY Specialty Lubricants**

manufactured by HUSK-ITT Corporation / SPECIALTY LUBRICANTS Corporation

### **Western Region Office:**

1580 Industrial Avenue, Norco, California 92860  
(951) 340-4000 • Fax: (951) 340-4011  
(888) 4-HUSKEY • [www.huskey.com](http://www.huskey.com)

### **Eastern Region Office:**

8300 Corporate Park Drive, Macedonia, Ohio 44056  
(330) 425-2567 • Fax: (330) 425-9637  
(800) 238-LUBE