



## Aircol SN 68 & 100

Synthetic Reciprocating Air Compressor oils

### Description

Aircol SN 68 and 100 are diester based synthetic lubricants with excellent oxidation resistance and low carbon-forming tendency.

### Application

Aircol SN 68 and 100 were developed to cope with the severe operating conditions experienced in reciprocating air compressors operating at high compression ratios and high discharge temperatures of up to 220 deg C. Under these conditions, Aircol SN 68 and 100 offer a much reduced carbon forming tendency and extended oil life when compared to mineral oil. Whilst Aircol SN 68 was primarily intended for the use in reciprocating air compressors, it may also be used in certain types of turbocharger, where it will provide significant in-service benefits when compared with mineral based lubricants.

### Features and Benefits

Castrol Aircol SN combines excellent protection, long life and cleanliness in operation to provide the following key benefits:

- Low carbon forming tendency giving longer valve life, longer intervals between cylinder head overhauls and greater reliability when operating at high discharge temperatures.
- Improved lubricity and film strength minimises cylinder and ring wear and also improves air quality by allowing feed rates to be reduced without detrimental results.
- Reduced compressor down time due to less wear on all moving parts, longer machine life and reduced maintenance.

## Technical Data

Name	Method	Units	Aircol SN 68	Aircol SN 100
ISO Viscosity Grade			68	100
Viscosity, Kinematic 40°C	ASTM D445	mm <sup>2</sup> /s	68	100
Viscosity, Kinematic 100°C	ASTM D-445	mm <sup>2</sup> /s	7.6	10.3
Viscosity Index			67	89
Relative Density @ 15°C		g/ml	0.96	0.96
Pour Point	ASTM D5950	°C	-40	-40
Flash Point, COC	ASTM D92	°C	>200	>200

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

## Care and Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

## Packaging and Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Aircol SN 68 & 100  
08 Oct 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

**Australia** Level 8 (QV1 Building), 250 St. Georges Terrace, Perth WA 6000, Australia. Customer Service Number +61 (0)8 9420 1854

**Dubai** City Tower 2, 6th Floor PO BOX 1699, Sheikh Zayed Road, Dubai, U.A.E. Customer Service Number +971 4 3079304

**Norway** Drammensveien 167, Box 153 Skoyen, 0212 Oslo, Norway. Customer Service Number +47 22 51 12 43

**Singapore** Keppel Bay Towers, 1 Harbourfront Avenue 02-01, Singapore 098632, Singapore. Customer Service Number +65 6371 8478

**United Kingdom** BlueSky Business Space, Westpoint House, Pavilion 2 Prospect Park, Prospect Road, Arnhall Business Park, Westhill. AB32 6FJ, UK.  
Customer Service Number +44 (0)1224 766900

**USA** 501 Westlake Park Boulevard, Houston, Texas 77079, USA. Customer Service Number +1 800 339-7157