

* PRODUCT INFORMATION *

CHUCK-EEZ[®] (Power Chuck Lubricant)

DESCRIPTION

CHUCK-EEZ[®] is a heavy-duty boundary lubricant designed to increase the clamping pressure of Power Chucks. **CHUCK-EEZ[®]** is formulated with a high percentage of molybdenum disulfide to reduce seizing, galling, fretting wear, and lower friction under conditions of extreme pressure. It is able to withstand pressures up to 500,000 pounds per square inch. The tacky nature of the product gives it high resistance to centrifuge force. Rust and oxidation inhibitors are incorporated to maximize complete rust protection during the life of the lubricant. **CHUCK-EEZ[®]** may also be used as an anti-seize lubricant on the fasteners when assembling the chuck.

USAGE

Power chucks, Standard Chucks, Fasteners, Press Fits, Wear-in and Guides & Ways.

ADVANTAGES

- Double to triple clamping pressure over conventional greases
- Keeps work piece clamped in place
- Reduces fretting wear
- Provides boundary lubrication protection
- Assists in wear-in of new chucks
- Lowers maintenance cost
- Lowers friction and wear
- High resistance to centrifuge force

METHOD OF APPLYING

Hand grease guns, pneumatic grease equipment. May be applied down to -20° F using a brush with stiff bristles or burnishing in with a clean cloth.



SLIPKOTE[®] Specialty Lubricants

manufactured by SPECIALTY LUBRICANTS Corporation / HUSK-ITT Corporation

Eastern Region Office:

8300 Corporate Park Drive, Macedonia, Ohio 44056
(330) 425-2567 • Fax: (330) 425-9637
(800) 238-5823 • www.speclubes.com

Western Region Office:

1580 Industrial Avenue, Norco, California 92860
(951) 340-4000 • Fax: (951) 340-4011
(888) 4-HUSKEY • www.huskey.com

TYPICAL PROPERTIES

Color	Moly Gray
Penetration, Unworked	290 to 315
NLGI No.	1.5
Base Oil Viscosity, cSt @ 40° C	216
cSt @ 100°C	12
Dropping Point °F	360
Flash Point °F	440
Pour Point °F	0
Base Grease, %	80 ± 0.5
Lubricating Solids, %	25 ± 0.2

SHIPPING LIMITATIONS

None

STORAGE/SHELF LIFE

When stored under normal warehouse condition, CHUCK-EEZ has no known limits on useful life. An oil layer may form on the top of the container. Stirring may readily mix it back in.

PACKAGE AVAILABILITY

4 oz. & 16 oz. Cartridges, 10 lb. Pail,
40 lb. Pail, 135 lb. Keg, 450 lb. Drum

The name of this product or group of products is for product identification purpose only. HUSK-ITT Corporation/SPECIALTY LUBRICANTS Corporation makes no warranties, representations or conditions of any kind expressed or implied, whether for merchantability or fitness with respect to these products. The final determination of the suitability of the products for the application contemplated by the user is the sole responsibility of the buyer. HUSK-ITT Corporation/SPECIALTY LUBRICANTS Corporation sales personnel are not authorized to amend this warranty limitation
10/09