
MOL Turbine 68 K

turbine oil

MOL Turbine 68 K is a premium turbine oil product having a low pour point, which is a balanced combination of carefully selected quality mineral oils and additives that inhibit oxidation and corrosion. It is particularly recommended for turbines and other industrial applications that require high reliability and long service lifetimes.

Application



	Steam, gas and water turbines of power plants, turbines with gear drives, turbocompressors
	Circulation systems
	Plain bearings exposed to dynamic water loads

Features and benefits

Outstanding thermal and hydrolytic stability	Very low deposit formation tendency Provides stick-free operation of servo and control valves Long oil drain intervals Reliable operation, so reduced operational costs
Outstanding filterability	No deterioration of filterability, even in the presence of moisture Calculably low filter usage even with 2-3 micron pore size filter cartridges
Rapid air release	Reduced risk of cavitation Outgoing air does not cause increased foaming Reliable operation, giving longer equipment lifetime
Extremely low foaming tendency	Forms a continuous, robust lubricating film even under forced operating conditions, giving reduced wear Longer lubricant and equipment lifetime
Excellent corrosion protection	Extreme long term protection of steel and non-ferrous metal parts even in the presence of moisture Long machine lifetime, so reduced maintenance cost
Excellent wear protection	Reliable operation in turbines fitted with a gearbox Improved operational safety and high level of availibility
Good water separation	Effective lubrication and problem-free operation even in the presence of water Abnormal corrosion and wear of equipment can be prevented Water accumulating at the bottom of the tank can be removed easily Longer oil change interval and equipment lifetime

Manufactured and distributed by MOL-LUB Ltd., 2931 Almásfüzitő, Fő út 21.
E-mail: lubricants@mol.hu Web: mollubricants.com
Technical service: H-1117 Budapest, Neumann János u. 1/E.
Tel: + 36 (1) 464-02-36 E-mail: lubtechdesk@mol.hu
Latest revision: 2024.11.08 14:39

Version: 007.022.000

MOL Turbine 68 K

turbine oil

Specifications and approvals

Viscosity grade: ISO VG 68
ISO 8068 Type AR
ISO-L-TGA
ISO-L-TSA
DIN 51515-1 L-TD
DIN 51524-1 (HL)
DIN 51517-2 (CL)
Cincinnati Lamb P-54
AIST (US Steel) 125
AIST (US Steel) 120
SKODA POWER
BS 489

Properties

Properties	Typical values
Density at 15°C [g/cm3]	0,881
Kinematic viscosity at 40°C [mm2/s]	68,2
Kinematic viscosity at 100 °C [mm2/s]	8,55
Pour point [°C]	-18
Flash point (Cleveland) [°C]	240
Neutralization number [mg KOH/g]	0,1
Air release properties at 50°C [min]	5
Water separability at 54°C	
- separation time at 54 °C [min]	10

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.
Keep away from direct flame and other sources of ignition.
Protect from direct sunlight.
During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.
For further details please read the Material Safety Data Sheet of the product.
In the original container under the recommended storage conditions: 48 months
Recommended storage temperature: max. 40°C

Manufactured and distributed by MOL-LUB Ltd., 2931 Almásfüzitő, Fő út 21.
E-mail: lubricants@mol.hu Web: mollubricants.com
Technical service: H-1117 Budapest, Neumann János u. 1/E.
Tel: + 36 (1) 464-02-36 E-mail: lubtechdesk@mol.hu