MOLYDUVAL Sekorex NAS Spray









Tacky Chain Lubricant Spray

A very tacky, high treated lubrication oilspray for chains, especially for outside door chains. Because of its good creeping characteristics it penetrates very good into the chain bolts and reduces wear. O-Ring compatible.

Contains tackifiers for better adhesion on fast running chains.

Properties

- * exceptional lubricating and separating properties
- * high pressure ability
- * strong tackiness
- * relative good compatible with elastomers and seals
- * provides protection against corrosion
- * excellent wear protection
- * rejects dirt

Applications

- * for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- * for chains in textile industry
- * for wire rope lubrication at cranes or containers
- * for motorcycle chains
- * for chains on bouw machines, lifters, mills
- * for chains in sensitive areas
- * for saw chains
- * for chains and wire ropes on ships

Technical Datas

Color brown Name **CLP1000** Base Fluid Min Density 15°C 900 kg/m³ Temperature Range °C -20 -> + 140 Viscosity 40°C 1000 mm²/s Viscosity Index 120

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.