



Tapmatic® AquaCut

Cutting Fluid



FEATURES

- Corrosion inhibitors prevent flash rusting
- Safe on all metals, except magnesium
- Does not contain sulfur, chlorine, or oils
- Non-hazardous
- Non-flammable
- Excellent in applications where cooling of the tool is desired
- Water-based formula
- Provides fine finishes

APPLICATIONS

- Boring
- Broaching
- Drawing
- Drilling
- Engraving
- Facing
- Grinding
- Finishing
- Stamping
- Tapping
- Threading
- Turning
- Milling
- Sawing

PROPERTIES

Appearance / Physical State	Liquid
Odor	Cinnamon
Melting / Freezing Point	Not established
Boiling Point / Range	212°F (100°C)
Vapor Pressure	18 mm Hg @ 20°C
Partition Coefficient	< 1
Percent volatile	95%
Flammability	None
Propellant	N/A
VOC Content	0 % per U.S. State and Federal Consumer Product Regulations CARB
Color	Blue green
Flash Point	None
Density	Not available.
Evaporation Rate	1 (water = 1)
Vapor density	-0.6
Auto-Ignition Temperature	> 33.8 °F (>1°C)
Viscosity	Not established
Specific Gravity	0.99 - 1.01 @ 20°C
Temperature Range	Not available.
4-Ball Weld Load	Not available.

DIRECTIONS

Apply a few drops of fluid just prior to contact. DO NOT USE IN MIST OR RECIRCULATING SYSTEMS.

HANDLING

Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
01216	C01216	16 fl oz / 473 mL	bottle	12	15 lbs
01228	C01228	1 gal / 3.78 L	bottle	4	37 lbs
01205	C01205	5 gal / 18.93 L	pail	1	48 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved