



ZeroTri® Heavy-Duty Degreaser



FEATURES

- Fast acting, heavy-duty solvent for degreasing metal parts and equipment
- Instantly cuts through grease, grime, oil, and other oil-based contaminants
- Fast evaporating, leaves no residue
- Does not contain chlorinated solvents
- Contoured can for improved hand grip

APPLICATIONS

- Bearings
- Bonding prep
- Chains
- Cranes
- Engines
- Forklifts
- Gears
- Machinery
- Printing Presses
- Pulleys
- Wire Cables

SPECIFICATIONS AND APPROVALS

- Boeing BAC 5750 Rev. J
- NSF International, C1 (Aerosol)
- NSF International, C1 (Bulk)
- Pratt & Whitney Canada MMC 21530

PROPERTIES

| | |
|------------------------------------|---------------------------------|
| Appearance / Physical State | Aerosol: Gas, Bulk: Liquid |
| Color | Colorless. Clear. |
| Odor | Ether-like. Fruity. |
| Melting / Freezing Point | Not established |
| Boiling Point / Range | > 132.8°F (> 56°C) |
| Flash Point | 1.4°F (-17.0 °C) Tag Closed Cup |
| Evaporation Rate | > 1 (BuAc = 1) |
| Flammability | Lower: 1.2%, Upper: 12.8% |
| Vapor Pressure | > 75 mm Hg @ 20°C |
| Vapor density | ~ 3 (air = 1) |
| Water Solubility | 35% w/w |
| Percent volatile | 100% |
| Specific Gravity | 0.74 - 0.76 @ 20°C |
| VOC Content | Aerosol: 62.4%, Bulk: 65% |
| Propellant | Carbon dioxide (Aerosol) |

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

"Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)"

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat and sources of ignition. (See Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

| US | Part No. | | Net Contents | Container Type | Units/Case | Approximate Case Weight |
|-------|----------|--------|---------------------------|----------------|------------|----------------------------|
| | Canada | Europe | | | | |
| 03520 | C03520 | M03520 | 15 wt oz / 425 g / 563 mL | aerosol | 12 | 15 lbs |
| 03528 | C03528 | | 1 gal / 3.78 L | can | 4 | 30 lbs |
| 03505 | C03505 | | 5 gal / 18.93 L | pail | 1 | 36 lbs |
| 03555 | C03555 | M03555 | 55 gal / 208 L | drum | 1 | 346 lbs |
| | | M03515 | 5 L | pail | 1 | |
| | | M03505 | 20 L | pail | 1 | |



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved